Reolink

P334

Smart 4K Ultra HD PoE Security IP Camera with Person/Vehicle Detection; IP66 Waterproof

- Person/Vehicle Detection
- 4K 8MP Ultra HD
- 100ft Night Vision

Specifications

Video & Audio	
Image Sensor	1/2.7" CMOS sensor
Video Resolution	3840X2160 (8.0 Megapixels) at 25 frames/sec
Lens	f=4.0mm fixed; F=2.0, with IR-cut filter
Video Compression	H.265
Field of View	Horizontal: 87°; Vertical: 44°
Day & Night	IR-cut filter with auto-switching
Night Vision	30 meters (100 ft) (LED: 18pcs/14mil/ 850nm)
Audio	Audio recording
Power	
PoE	IEEE 802.3af, 48V Active
DC Power	DC 12.0V 1A, <12W
Interface	

Power	DC power port
System	Reset button
Ethernet	One 10M/100Mbps; RJ45
Storage	microSD card slot (Max. 256GB)
Audio	Built-in microphone
Software Features	
Frame Rate	Mainstream: 2fps - 25fps (default: 25fps); Substream: 4fps - 15fps (default: 10fps)
Code Rate	Mainstream: 4096Kbps - 8192Kbps (default: 6144Kbps); Substream: 64Kbps - 512Kbps (default: 256Kbps)
Browser Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	Motion detection; Person/vehicle/ animal detection
Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximal User Access	20 users (1 admin account & 19 user accounts); support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Smart Home	Google Assistant
Working Environment	
Temperature	-10°C ~ +55°C (14°F ~ 131°F)
Humidity	10% ~ 90%
Weatherproof	IP67
Size & Weight	
Dimensions	Φ105*95mm

Weight	467.5g
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/

Gallery & Specs



1. Mount
2. Metal Aluminum Case
3. Spotlight
4. IR LEDs
5. High Definition Lens
6. Daylight Sensor



Only Manual Rotation



1. Power
2. Reset
3. Network
4. Waterproof Lid